

CERTIFICATE OF MAILING BY FIRST CLASS MAIL (37 CFR 1.8)Applicant(s): **Yoshinori NISHIWAKI et al.**

Docket No.

2002JP314D

Serial No.

10/532,364

Filing Date

April 20, 2005

Examiner

To Be Assigned

Group Art Unit

To Be AssignedInvention: **CHEMICALLY AMPLIFIED POSITIVE PHOTSENSITIVE RESIN COMPOSITION**I hereby certify that this **English Language abstract of JP 2001-281863 - 2 Pages***(Identify type of correspondence)*

is being deposited with the United States Postal Service as first class mail in an envelope addressed to: The

Commissioner of Patents and Trademarks, Washington, D.C. 20231-0001 on **September 21, 2005***(Date)***MARIA T. SANCHEZ***(Typed or Printed Name of Person Mailing Correspondence)*A handwritten signature in cursive script, appearing to read "Maria T. Sanchez".
*(Signature of Person Mailing Correspondence)***Note: Each paper must have its own certificate of mailing.**

BEST AVAILABLE COPY

(11)Publication number : **2001-281863**

(43)Date of publication of application : 10.10.2001

(51)Int.Cl. G03F 7/039

C08J 5/18

C08L 29/10

C08L101/02

G03F 7/004

G03F 7/033

G03F 7/38

G03F 7/40

G03F 7/42

H01L 21/027

(21)Application number : 2000-090853 (71)Applicant : JSR CORP

(22)Date of filing : 29.03.2000 (72)Inventor : OTA KATSU

ITO JUNJI

IWANAGA SHINICHIRO

(54) RADIATION SENSITIVE RESIN COMPOSITION AND METHOD FOR
PRODUCING PLATED/SHAPED BODY

(57)Abstract:

PROBLEM TO BE SOLVED: To provide a positive type radiation sensitive resin composition giving a pattern free of cracking even in plating and even by washing and drying after plating, capable of precisely forming a thick plated/shaped body such as a bump or wiring and excellent also in sensitivity, resolution, etc., and a method for producing the plated/shaped body using the composition.

SOLUTION: The positive type radiation sensitive resin composition contains (A) a polymer having an acid dissociable functional group which is dissociated by an acid to

form an acidic functional group, (B) a poly(vinyl lower alkyl ether), (C) a component which generates the acid when irradiated and (D) an organic solvent. The composition is also used as a positive type radiation sensitive resin film. The plated/shaped body is produced through a step for carrying out electroplating using a pattern formed on a substrate from the composition or the resin film as a template.

LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]